



ADX.0270

SANAFAST

Setting and hardening
accelerator

Customs Code

3824 5090

Packaging

- Bag 25 kg
- Pail 10 kg

Application

- To be added to other components

Family
Admix

Type
Multifunctional powder additives/concentrates for packaging injectable slurry, dehumidifying plasters and accelerating admixtures for the hold of mortars and plasters

Product Lines
• Building
• Opus

Functional Categories
• **Improvement of mechanical and/or rheological performance of newly manufactured mortars, plasters and concretes**

Components
Single-component

Appearance
Powder

General description

SANAFAST is a specially formulated premix that, added during the mixing phase to our mortars (REPAR, GROUT, FLOOR, RINFOR lines) and to our natural hydraulic lime-based injection products (SANAFUENS, MIKROSANA), allows to accelerate the setting and hardening, with a much faster development of mechanical strength.

General features

SANAFAST is formulated with a fast-setting binder and very fine mineral fillers, perfectly compatible with Portland cements, pozzolanic cements and natural hydraulic lime.

Dosage

SANAFAST can be mixed in any proportion with any hydraulic binder.

Fields of application

Adaptation (acceleration) of the setting times of mortars and plasters, to be used when environmental and meteorological conditions would make them too "slow" compared to the requirements of use: for example in the winter period when temperatures are low.

Basic features



Nonflammable



Shelf-life:
12 months



Temperature of use:
+5 / +35 °C



Use wearing protective gloves



Available colours
White

Tools cleansing

- Water

Applicable on

- Cement-based or lime-based mortars

Instructions for use

Careful dry premixing of SANAFAST with the product for which an acceleration of setting and hardening times is always recommended.

Storage and preservation

Store the product in its original packing, in a fresh and dry environment, avoiding frost and direct sunlight. Inadequate storage of the product may result in a loss of rheological performance. Protect from humidity.



www.azichem.com

Updated: 25/01/2022

General sales conditions and legal notices on

www.azichem.com/disclaimer



Warnings, Precautions and Ecology

The general information, along with any instructions and recommendations for use of this product, including in this data sheet and eventually provided verbally or in writing, correspond to the present state of our scientific and practical knowledge.

Any technical and performance data reported is the result of laboratory tests conducted in a controlled environment and thus may be subject to modification in relation to the actual conditions of implementation.

Azichem Srl does not assume any liability arising from inadequate characteristics related to improper use of the product or connected to defects arising from factors or elements unrelated to the quality of the product, including improper storage.

Those wishing to utilise the product are required to determine prior to use whether or not the same is suitable for the intended use, assuming all consequent responsibility.

The technical and characteristic details contained in this data sheet shall be updated periodically. For consultation in real time, please visit the website: www.azichem.com. The date of revision is indicated in the space to the side. The current edition cancels out and replaces any previous version.

Please note that the user is required to read the latest Safety Data Sheet for this product, containing chemical-physical and toxicological data, risk phrases and other information regarding the safe transport, use and disposal of the product and its packaging. For consultation, please visit: www.azichem.com.

It is forbidden to dispose of the product and/or packaging in the environment.

SANAFAST is produced/distributed by



Via Giovanni Gentile, 16/A - 46044 Goito (MN), Italy
info@azichem.com Tel. +39 0376.604185 /604365 Fax +39 0376 604398



www.azichem.com

Updated: **25/01/2022**
General sales conditions and legal
notices on
www.azichem.com/disclaimer