

# CSX.0119 CONSILEX MUFFA CLEANER

Cleaning, descaling, with antimildew agent



2923 9000



- Bottle 1 l
- Plastic can 5 l
- Plastic can 25 l

# Application

- Low pressure airless nebulizer
- Brush
- Sprayer

Family Consilex

Type

Cleaning solutions based on bland acids with anti-mildew

Product Lines

BuildingOpusSanageb

Functional Cathegories

• Reconstruction, repair and maintenance of wooden

Ecologic treatments with anti-fungal

Deep cleaning of supports

Components
Single-component

Appearance Liquid

structures

# General description

Transparent, ready-to-use cleaning agent, for the safe removal of scale blackish incrustations from moulds and biodeteriogenic manifestations, as well as for the revitalising renewal of wooden surfaces.

#### General features

It is particularly recommended for the cleaning and removal of the brown and blackish incrustations caused by humidity and mould, on masonry, internal and external plasters, chalk coatings, lime, cement, paint, plastic, wooden surfaces. It can be used effectively also for the restoration and renewal of wooden surfaces degraded and blackened by humidity and the weather.

## **Dosage**

Approximately 0.20 litres of CONSILEX MUFFA CLEANER for every square metre of surface to be treated.

## Fields of application

Cleaning and removal of deposits and stains caused by moulds and biodeteriogenic manifestations. Renovation and maintenance of wooden surfaces degraded by moulds and moisture.

#### Basic **features**



Material 100% eco-friendly



Nonflammable



Shelf-life: 12 months



Solvent-free



Use wearing protective glasses



Use wearing protective gloves



**UV-resistant** 



Available **colours** Transparent

# Tools **cleansing**

• Water

#### Plasters

- Concrete
- Cement-based or lime-based mortars
- Drywall
- Plaster (gypsum)

Applicable on

- Wood
- Bricks
- Tuff
- Mixed walls (bricks and stones)
- · Brickworks
- Stone walls



www.azichem.com

Updated: **24/08/2020**General sales conditions and legal

notices on

www.azichem.com/disclaimer

Page: 1/3

#### **Instructions** for use

AS A CLEANING, DAMP PROOFING AGENT:

Apply the product by spraying or brushing the surfaces to be cleaned, leave to work for a period of time ranging from 30 minutes to one hour; then remove the product with a sponge and rinse with water. In the case of particularly resistant concretions, repeat the operations described until their complete elimination.

#### AS WOOD RENEWER:

For surface cleaning, for example, before repainting, apply the product until rejection on soiled and/or blackened parts, with a sprayer or a brush. Remove the product after a few minutes with a damp sponge or brush with water. For a deeper treatment, to renew the original natural appearance of wood, leave the product to work for at least 12 hours. Then proceed with the removal of fouling with a brush and water and, after drying, proceed with the protective repainting with appropriate flatting or with transparent paints.

## **Storage** and preservation

Protect from freezing. Store the product in its original packing, in a fresh and dry environment, avoiding frost and direct sunlight. Inadequate storage of the product may result in a loss of rheological performance. Store the product at a temperature between  $+5^{\circ}$ C and  $+35^{\circ}$ C.

# Warnings, Precautions and Ecology

The general information, along with any instructions and recommendations for use of this product, including in this data sheet and eventually provided verbally or in writing, correspond to the present state of our scientific and practical knowledge.

Any technical and performance data reported is the result of laboratory tests conducted in a controlled environment and thus may be subject to modification in relation to the actual conditions of implementation.

Azichem Srl does not assume any liability arising from inadequate characteristics related to improper use of the product or connected to defects arising from factors or elements unrelated to the quality of the product, including improper storage.

Those wishing to utilise the product are required to determine prior to use whether or not the same is suitable for the intended use, assuming all consequent responsibility.

The technical and characteristic details contained in this data sheet shall be updated periodically. For consultation in real time, please visit the website: www.azichem.com. The date of revision is indicated in the space to the side. The current edition cancels out and replaces any previous version.

Please note that the user is required to read the latest Safety Data Sheet for this product, containing chemical-physical and toxicological data, risk phrases and other information regarding the safe transport, use and disposal of the product and its packaging. For consultation, please visit: www.azichem.com.

It is forbidden to dispose of the product and/or packaging in the environment.



Updated: 24/08/2020

www.azichem.com

General sales conditions and legal

notices on

www.azichem.com/disclaimer

Page: 2/3





www.azichem.com

Updated: **24/08/2020** 

General sales conditions and legal

notices on

www.azichem.com/disclaimer

Page: **3/3**