



CSX.0161

SANASTARK

Curing solution, for powdery bedding plasters, mortars and stones

Customs Code

3824 9970

Packaging

- Plastic can 5 kg
- Plastic can 10 kg
- Plastic can 25 kg

Application

- Low pressure airless nebulizer
- Brush
- Sprayer

Family
Consilex

Type
Consolidating treatments and porosity reducers for concretes, plasters and stone works

Product Lines
• **Building**
• **Opus**
• **Sanageb**

Functional Categories
• **Surface strengthening of masonry and plasters**
• **Masonry plastering with plasters and skims**
• **Renewal of wet masonry with waterproofing plasters**
• **Fixing treatments to be applied before varnishing and coating**
• **Decorative, strengthening joints of exposed masonry**

Components
Single-component

Appearance
Liquid

General description

Reactive solution of mineral silicates, capable of forming binding and stabilizing compounds for hardening and consolidating treatments by reaction with hydrated calcium salts and moisture present in masonry, plaster, stone and concrete. Indicated in the preliminary treatments to the subsequent plastering or smoothing operations, of plasters and powdery mortars and wall casings in general, in green building interventions and in the restoration of period and monumental buildings.

General features

SANASTARK is a solution based on mineral silicates, demineralised water and natural dispersant. It does not contain traces of resins, solvents or thinners. The application of SANASTARK does not affect the original wall breathability.

Dosage

From 0.20 to 0.30 kg of SANASTARK for each square metre of surface to be treated, based on the porosity of the support.

Fields of application


Cortical reinforcement and elimination of pulverisation of mortars, plasters and masonry jointing. Also suitable as a natural fixative before applying lime putty- or potassium silicate-based plasters and paints.

Basic features


 Density:
1.03 kg/dm³

 Material 100% eco-friendly

 Nonflammable


 Shelf-life:
12 months

 Solvent-free

 Temperature of use:
+8 / +30 °C

 Use wearing protective glasses

 Use wearing protective gloves

 Available colours
Transparent

Tools cleansing

- Water

Applicable on

- Plasters
- Cement-based or lime-based mortars
- Bricks
- Mixed walls (bricks and stones)
- Stone walls

IF YOU WANT TO SOLVE IT
 **azichem**

www.azichem.com

Updated: **06/07/2021**
General sales conditions and legal notices on
www.azichem.com/disclaimer

Substrate preparation

Remove the soilings and saline manifestations by vigorous brushing. Then eliminate the residual dust. Saturate with water until you reach the condition of "saturated with dry surface".

Instructions for use

Apply by spraying, proceeding from the bottom up; it can also be applied with a brush with natural long bristles. In the presence of pronounced degradations proceed with several applications, wet on wet.

Storage and preservation

Protect from freezing. Store the product in its original packing, in a fresh and dry environment, avoiding frost and direct sunlight. Inadequate storage of the product may result in a loss of rheological performance. Store the product at a temperature between +5°C and +35°C.



Warnings, Precautions and Ecology

The general information, along with any instructions and recommendations for use of this product, including in this data sheet and eventually provided verbally or in writing, correspond to the present state of our scientific and practical knowledge.

Any technical and performance data reported is the result of laboratory tests conducted in a controlled environment and thus may be subject to modification in relation to the actual conditions of implementation.

Azichem Srl does not assume any liability arising from inadequate characteristics related to improper use of the product or connected to defects arising from factors or elements unrelated to the quality of the product, including improper storage.

Those wishing to utilise the product are required to determine prior to use whether or not the same is suitable for the intended use, assuming all consequent responsibility.

The technical and characteristic details contained in this data sheet shall be updated periodically. For consultation in real time, please visit the website: www.azichem.com. The date of revision is indicated in the space to the side. The current edition cancels out and replaces any previous version.

Please note that the user is required to read the latest Safety Data Sheet for this product, containing chemical-physical and toxicological data, risk phrases and other information regarding the safe transport, use and disposal of the product and its packaging. For consultation, please visit: www.azichem.com.

It is forbidden to dispose of the product and/or packaging in the environment.

It can cause the opacification of aluminium surfaces, glass, ceramised tiles etc. which must therefore be protected during application.

Do not apply on mineral surfaces (plaster, bricks etc.), destined to remain exposed, without carrying out a preliminary test, as there is a risk of latent salt crystallisation.

SANASTARK is a moderately caustic solution at the implementation stage: do not ingest, wear protective gloves, goggles and clothing, take the necessary precautions.



www.azichem.com

Updated: 06/07/2021

General sales conditions and legal notices on

www.azichem.com/disclaimer

SANASTARK is produced/distributed by



Via Giovanni Gentile, 16/A - 46044 Goito (MN), Italy
info@azichem.com Tel. +39 0376.604185 /604365 Fax +39 0376 604398



www.azichem.com

Updated: **06/07/2021**
General sales conditions and legal
notices on
www.azichem.com/disclaimer

Page: **3/3**