



CSX.0184

STUCCO BALCONY

Two-component cement surfacer,
waterproof, high adherence

Customs Code

3824 5090

Packaging

- Pail 4 kg [A]
- Bucket 0.8 kg [A]
- Bottle 1 kg [B]
- Bucket 0.2 kg [B]
- Kit: 1 Pail 4 kg [A] + 1 Bottle 1 kg [B]
- Kit: 1 Bucket 0.8 kg [A] + 1 Bucket 0.2 kg [B]

Application

- Spatula
- Apply by hand
- Sponge float
- Sponge

Family
Consilex

Type
Transparent, non-film waterproofing and relative products
for terraces and balconies

Product Lines
• Aqua
• Building

Functional Categories
• Bonding and filling tiles, parquet, etc.
• Transparent waterproofing of tiled terraces and balconies

Components
Two-components

Appearance
Powder + Liquid

General description

A two-component, fine cementitious grout with a fluid plastic consistency for grouting uncovered joints or filling and finishing static cracks, micro- and macro-cavities and so on between flooring tiles, before applying PROTECH BALCONY for breathable non-film waterproofing operations on terraces and balconies.










Dosage

Approximately 1.75 kg of STUCCO BALCONY for each cubic decimetre of volume to be grouted.

Fields of application

Specific putty for the preliminary preparation of supports (open gaps, micro and macro-cavities and fissures) for the subsequent application of PROTECH BALCONY on terraces and balconies.

Basic features

-  Max. recommended thickness:
6 mm
-  Maximum diameter of aggregate:
0.35 mm
-  Nonflammable
-  Pot-life:
15 - 20 min
-  Shelf-life:
12 months
-  Temperature of use:
+5 / +35 °C
-  Use wearing protective gloves
-  UV-resistant
-  Available colours
Light gray

Technical specifications

Capillary absorption (UNI EN 13057): 0.10 kg•h^{0.5}/m²

Complete hardening (a 20°C): 180 min

Mixing ratio of the components A:B: 4:1 _

Tools cleansing

- Water

Applicable on

- Tiles

Substrate preparation

Application surfaces should be clean, free of soiling, crumbling and non-adhering parts, dust, etc., conveniently saturated with water until they reach the condition "saturated with dry surface".



www.azichem.com

Updated: 30/11/2021

General sales conditions and legal
notices on

www.azichem.com/disclaimer

Instructions for use

Add the quantity of component B required to obtain the desired consistency to component A; mix thoroughly until a homogeneous lump-free mixture is obtained. Place on site using a spatula, sponge float or simply with the fingers of the hand (wearing a rubber glove).

It is possible to correct the consistency, where necessary, by adding moderate quantities of water to the ready mixture.

In the cases of coloured surfacings, it is recommended to mix the two-component with small amounts of coloured pigments that can be purchased at any paint shop.

Storage and preservation

Protect from freezing. Store the product in its original packing, in a fresh and dry environment, avoiding frost and direct sunlight. Inadequate storage of the product may result in a loss of rheological performance. Store the product at a temperature between +5°C and +35°C.



Warnings, Precautions and Ecology

The general information, along with any instructions and recommendations for use of this product, including in this data sheet and eventually provided verbally or in writing, correspond to the present state of our scientific and practical knowledge.

Any technical and performance data reported is the result of laboratory tests conducted in a controlled environment and thus may be subject to modification in relation to the actual conditions of implementation.

Azichem Srl does not assume any liability arising from inadequate characteristics related to improper use of the product or connected to defects arising from factors or elements unrelated to the quality of the product, including improper storage.

Those wishing to utilise the product are required to determine prior to use whether or not the same is suitable for the intended use, assuming all consequent responsibility.

The technical and characteristic details contained in this data sheet shall be updated periodically. For consultation in real time, please visit the website: www.azichem.com. The date of revision is indicated in the space to the side. The current edition cancels out and replaces any previous version.

Please note that the user is required to read the latest Safety Data Sheet for this product, containing chemical-physical and toxicological data, risk phrases and other information regarding the safe transport, use and disposal of the product and its packaging. For consultation, please visit: www.azichem.com.

It is forbidden to dispose of the product and/or packaging in the environment.

Do not apply in case of direct exposure to sunlight. Cure the prolonged moist hardening of exposed surfaces.

Given the high adherence and rapid drying of the product, it is advisable to wash the excess parts of the surfacings immediately after application, with a sponge impregnated with water, ("smudges") to avoid tedious cleaning

In transparent non-pellicular waterproofing interventions of terraces and balconies, STUCCO BALCONY must only be applied to restore the continuity of labile, detached or missing puttying. For this reason, the consumption is extremely variable from case to case, depending on the actual volume of filling to be performed.



www.azichem.com

Updated: 30/11/2021

General sales conditions and legal notices on

www.azichem.com/disclaimer

STUCCO BALCONY is produced/distributed by



Via Giovanni Gentile, 16/A - 46044 Goito (MN), Italy
info@azichem.com Tel. +39 0376.604185 /604365 Fax +39 0376 604398



www.azichem.com

Updated: **30/11/2021**
General sales conditions and legal
notices on
www.azichem.com/disclaimer

Page: **3/3**