

FLR.0120

QL FLUOSIL

Anti-dust chemical hardener for concrete floors and screeds



3824 9970

Packaging

- Plastic can 25 kg
- Plastic can 5 kg

Application

- Scrubbing brush
- Scrubber-dryer machine

Family Ty
Floortech Con

Consolidating, dust-resistant and water-oil repellent

treatments in an aqueous solution

Product Lines Functional Cathegories

Infratech
 Construction of high performance industrial concrete
 Sanageb
 floors

• Floor
• Wall structure treatments and repair of industrial concrete floors

Components Appearance

Single-component Liquid

General description

An anti-dust chemical/mechanical revitalising hardener for concrete flooring and screeds, consisting of an aqueous solution of mineral silicates and fluosilicates, activated by specific wetting agents. It is applied in several coats of decreasing dilution in water, with a brush or mechanical "scrubber". Specific anti-dust treatments for industrial flooring or concrete slabs that have lost their original "vitality".

General **features**

It reacts with the calcium compounds, soluble and unstable, present in of concrete products, transforming them into new stable, insoluble and resistant compounds. Consequent increases in resistance to wear and tear of the order of 200% -400%, significant increases in chemical stability, resistance to freeze-thaw cycles etc.

Dosage

Apply from 0.25 to 0.40 kg of QL FLUOSIL per square metre of surface to be treated.

Fields of application

Reactive impregnations for stabilising chemical and mechanical structures and concrete products. Hardening, anti-dust, anti abrasive and anti-corrosion treatments for concrete floorings. Adjustment of the chemical and mechanical performance of products for the industrial, rural and livestock construction (on horizontal surfaces).

Basic **features**

KG

Density: 1.13 kg/dm³



Nonflammable



Shelf-life: 12 months



Solvent-free



Temperature of use: +5/+35 °*C*



To be applied in three coats



Use wearing protective glasses



Use wearing protective gloves



Available **colours** Transparent

Tools **cleansing**

Water

Applicable on

- Concrete
- · Floor screed

Substrate **preparation**

Application surfaces should be clean, free of soiling, crumbling and non-adhering parts, dust, etc., conveniently saturated with water until they reach the condition "saturated with dry surface".



www.azichem.com

Updated: 30/11/2021
General sales conditions and legal

notices on

www.azichem.com/disclaimer

Page: 1/3

Instructions for use

Apply, preferably with a brush or with "washer dryer" machine on the basis of the following indications:

- Porous surfaces: repeated applications of a solution of water and QL FLUOSIL at a ratio in 1:1
- Compact surfaces: apply three coats, with decreasing dilution with water. 1a coat 1:3, 2a coat 1:2, 3a coat 1:1.

The consumption of QL FLUOSIL will be proportional to the absorption of the floor to be treated. Indicatively a porous surface will consume about 400 g/m^2 , while a surface with normal porosity will consume $250\text{-}300 \text{ g/m}^2$.

Leave the product to dry between one coat and the next and then, after the last coat, wash with copious amounts of water. Protect glass and aluminium surfaces during application.

Storage and preservation

Protect from freezing. Store the product in its original packing, in a fresh and dry environment, avoiding frost and direct sunlight. Inadequate storage of the product may result in a loss of rheological performance.



Warnings, Precautions and Ecology

The general information, along with any instructions and recommendations for use of this product, including in this data sheet and eventually provided verbally or in writing, correspond to the present state of our scientific and practical knowledge.

Any technical and performance data reported is the result of laboratory tests conducted in a controlled environment and thus may be subject to modification in relation to the actual conditions of implementation.

Azichem Srl does not assume any liability arising from inadequate characteristics related to improper use of the product or connected to defects arising from factors or elements unrelated to the quality of the product, including improper storage.

Those wishing to utilise the product are required to determine prior to use whether or not the same is suitable for the intended use, assuming all consequent responsibility.

The technical and characteristic details contained in this data sheet shall be updated periodically. For consultation in real time, please visit the website: www.azichem.com. The date of revision is indicated in the space to the side. The current edition cancels out and replaces any previous version.

Please note that the user is required to read the latest Safety Data Sheet for this product, containing chemical-physical and toxicological data, risk phrases and other information regarding the safe transport, use and disposal of the product and its packaging. For consultation, please visit: www.azichem.com.

It is forbidden to dispose of the product and/or packaging in the environment.

QL FLUOSIL can be applied on concrete building supports that have a life of at least 30 days. It is not recommended to use QL FLUOSIL in the case of coloured concrete industrial floorings; in these cases, we recommend the use of QL NANO LITHIUM.

Caution, it is a moderately caustic and corrosive product.



Updated: 30/11/2021

General sales conditions and legal

notices on

www.azichem.com/disclaimer

Page: 2/3





www.azichem.com

Updated: **30/11/2021**General sales conditions and legal

notices on

www.azichem.com/disclaimer

Page: **3/3**