



FLR.0377

## PRERIT SURFACE

Water-oil repellent solution for  
washed gravel floors

### Customs Code

3824 9970

### Packaging

- Plastic can 5 kg
- Plastic can 25 kg
- Plastic can 10 kg

### Application

- Suffuse
- Low pressure airless nebulizer
- Sprayer

Family  
**Floortech**

Product Lines

- Aqua
- Building
- Opus
- Sanageb
- Floor

Components  
**Single-component**

Type  
**Architectural flooring in washed gravel and correlated products**

Functional Categories

- **Improvement of waterproofing capacity and/or impermeabilisation of mortars, plasters and concretes**
- **Liquid waterproofing of cementitious products**

Appearance  
**Liquid**

## General description

An impregnating water-oil repellent that is colourless, non-film and based on the nano-dispersion of silicon compounds. Protects washed gravel floors from the weather, frost and thaw cycles, and aggressive atmospheric conditions. It does not alter the colour of the support nor impact the original appearance or breathability. Also to be used, as a stain prevention during the washing operations of the surface to be deactivated, on the artifacts around the architectural flooring.

## General features

PRERIT SURFACE belongs to the new generation of water-soluble fluorinated silica compounds, characterised by zero emissions of VOCs and the absence of flammability and toxicity. The active substance penetrates the porosity, adhering to the support and counteracting the penetration and advancement of liquids without blocking the breathability of the support.

The special chemical structure of PRERIT SURFACE ensures its high stability to alkali and thus its durability over time.

The product differs from other treatments on the market due to having the following characteristics:

- non-flammable
- non-film
- zero VOC
- stable in water
- free from emulsifiers
- environmentally-friendly
- durability over time
- total transparency
- no variations to the surface colour
- excellent water vapour breathability
- elevated pearl effect
- resistance to acids and alkalis
- resistance to UV rays
- an absence of reactive by-products that are harmful to people and the environment

## Dosage

From 0.10 to 0.15 kg of PRERIT SURFACE per square metre of surface to be treated.


## Fields of application

Impregnating, hydro-oil repellent, non-film, totally transparent, colorless treatment of FLOORTECH PRERIT washed gravel architectural floors.

## Basic features


 Nonflammable

 Shelf-life:  
12 months

 Solvent-free

 Use wearing protective glasses

 Use wearing protective gloves

 Available colours  
Transparent

IF YOU WANT TO SOLVE IT  
 **azichem**

[www.azichem.com](http://www.azichem.com)

Updated: **26/11/2021**  
General sales conditions and legal  
notices on  
[www.azichem.com/disclaimer](http://www.azichem.com/disclaimer)

# Technical specifications

Flash-point: > 95 °C

Odorless

pH: 6.5 \_

The product doesn't create film

## Tools cleansing

- Water

## Applicable on

- Concrete
- Prefabricated concrete

## Substrate preparation

It is recommended that surfaces be treated prior to remove soluble salts and dirt, along with parts with poor surface adhesion. Cracks greater than 0.3 mm must always been filled. Apply to dry surfaces. In the event of rain or surface washing, wait 3 days at a temperature of at least 20° C prior to treatment.

## Instructions for use

Apply the product homogeneously and evenly, by spraying at low pressure or brushing, taking care to achieve the best saturation of the substrate.

PRERIT SURFACE comes ready-to-use. The quantity of product required depends on the porosity and absorption of the substrate to be treated, generally ranging from 100 to 150 grams/square metre.

## Storage and preservation

Protect from freezing. Store the product in its original packing, in a fresh and dry environment, avoiding frost and direct sunlight. Inadequate storage of the product may result in a loss of rheological performance. Store the product at a temperature between +5°C and +35°C.



## Warnings, Precautions and Ecology

The general information, along with any instructions and recommendations for use of this product, including in this data sheet and eventually provided verbally or in writing, correspond to the present state of our scientific and practical knowledge.

Any technical and performance data reported is the result of laboratory tests conducted in a controlled environment and thus may be subject to modification in relation to the actual conditions of implementation.

Azichem Srl does not assume any liability arising from inadequate characteristics related to improper use of the product or connected to defects arising from factors or elements unrelated to the quality of the product, including improper storage.

Those wishing to utilise the product are required to determine prior to use whether or not the same is suitable for the intended use, assuming all consequent responsibility.

The technical and characteristic details contained in this data sheet shall be updated periodically. For consultation in real time, please visit the website: [www.azichem.com](http://www.azichem.com). The date of revision is indicated in the space to the side. The current edition cancels out and replaces any previous version.

Please note that the user is required to read the latest Safety Data Sheet for this product, containing chemical-physical and toxicological data, risk phrases and other information regarding the safe transport, use and disposal of the product and its packaging. For consultation, please visit: [www.azichem.com](http://www.azichem.com).

It is forbidden to dispose of the product and/or packaging in the environment.

*PRERIT SURFACE is produced/distributed by*



Via Giovanni Gentile, 16/A - 46044 Goito (MN), Italy  
info@azichem.com Tel. +39 0376.604185 /604365 Fax +39 0376 604398



[www.azichem.com](http://www.azichem.com)

Updated: **26/11/2021**  
General sales conditions and legal  
notices on  
[www.azichem.com/disclaimer](http://www.azichem.com/disclaimer)