

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : REPAR TIX SPEEDY HP  
Revision date : 28.04.2017  
Print date : 28.04.2017

Version (Revision) : 2.0.0 (1.0.0)

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

REPAR TIX SPEEDY HP

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses

Construction and Construction Preparation: Rheoplastic, Structural, Fibrinated, Reinforced Malt, Reliable Stretchability and Quick Hardening Evolution

#### 1.3 Details of the supplier of the safety data sheet

**Producer/supplier :** AZICHEM S.r.l.  
**Street :** Via G.Gentile, 16/A  
**Postal code/city:** 46044 GOITO (MN) Italy  
**Telephone :** +39 0376 604185/604365  
**Fax :** +39 0376 604398  
**Information contact:** info@azichem.com

#### 1.4 Emergency telephone number

Centro Antiveleni di Milano +39 02 66101029 (CAV Ospedale Niguarda Ca' Granda -Milano) (24h)  
Centro Antiveleni di Pavia +39 0382 24444 (CAV IRCCS Fondazione Maugeri - Pavia)  
Centro Antiveleni di Bergamo +39 800 883300 (CAV Ospedali Riuniti - Bergamo)  
Centro Antiveleni di Firenze +39 055 7947819 (CAV Ospedale Careggi - Firenze)  
Centro Antiveleni di Roma +39 06 3054343 (CAV Policlinico Gemelli - Roma)  
Centro Antiveleni di Roma +39 06 49978000 (CAV Policlinico Umberto I - Roma)  
Centro Antiveleni di Napoli +39 081 7472870 (CAV Ospedale Cardarelli - Napoli)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Eye Dam. 1 ; H318 - Serious eye damage/eye irritation : Category 1 ; Causes serious eye damage.

Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.

Skin Sens. 1 ; H317 - Skin sensitisation : Category 1 ; May cause an allergic skin reaction.

STOT SE 3 ; H335 - STOT-single exposure : Category 3 ; May cause respiratory irritation.

#### 2.2 Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

###### Hazard pictograms



Corrosion (GHS05) · Exclamation mark (GHS07)

###### Signal word

Danger

###### Hazard components for labelling

CEMENT, PORTLAND, CHEMICALS ; CAS No. : 65997-15-1

###### Hazard statements

H318 Causes serious eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H335 May cause respiratory irritation.

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : REPAR TIX SPEEDY HP  
Revision date : 28.04.2017  
Print date : 28.04.2017

Version (Revision) : 2.0.0 (1.0.0)

### Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P264 Wash hands thoroughly after handling.  
P310 Immediately call a POISON CENTER/doctor  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

### 2.3 Other hazards

None

## SECTION 3: Composition / information on ingredients

### 3.2 Mixtures

#### Hazardous ingredients

CEMENT, PORTLAND, CHEMICALS ; EC No. : 266-043-4; CAS No. : 65997-15-1

Weight fraction :  $\geq 30 - < 40$  %

Classification 1272/2008 [CLP] : Eye Dam. 1 ; H318 Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 STOT SE 3 ; H335

#### Additional information

Full text of H- and EUH-statements: see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

When in doubt or if symptoms are observed, get medical advice.

#### Following inhalation

Remove victim out of the danger area. Symptoms may develop several hours following exposure; medical observation therefore necessary for at least 48 hours.

#### In case of skin contact

Wash immediately with: Water Remove contaminated, saturated clothing immediately. In case of skin irritation, consult a physician. In case of skin reactions, consult a physician.

#### After eye contact

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

#### After ingestion

Never give anything by mouth to an unconscious person or a person with cramps.

### 4.2 Most important symptoms and effects, both acute and delayed

On contact with moist skin may cause thickening, cracking and cracking of the skin. Prolonged contact in combination with existing abrasions can cause burns. Direct contact with the product may cause corneal injury due to mechanical stress, immediate or delayed irritation or inflammation. The direct contact with large quantities of product dry or with projections of wet product can cause effects ranging from irritation ocular moderate (eg. Conjunctivitis or blepharitis) to chemical burns and blindness. Dust may irritate throat and respiratory system. Coughing, sneezing and panting may occur as a result of exposure above the occupational exposure limits. May cause an allergic skin reaction.

### 4.3 Indication of any immediate medical attention and special treatment needed

None

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Extinguishing powder alcohol resistant foam Carbon dioxide (CO<sub>2</sub>) Water mist

### 5.2 Special hazards arising from the substance or mixture

None

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : REPAR TIX SPEEDY HP  
Revision date : 28.04.2017  
Print date : 28.04.2017

Version (Revision) : 2.0.0 (1.0.0)

### 5.3 Advice for firefighters

Remove persons to safety.

#### Special protective equipment for firefighters

Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Clear spills immediately. Wear a self-contained breathing apparatus and chemical protective clothing.

#### For non-emergency personnel

Remove persons to safety.

### 6.2 Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

### 6.3 Methods and material for containment and cleaning up

#### For containment

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal.

#### For cleaning up

The contaminated area should be cleaned up immediately with: Water Retain contaminated washing water and dispose it.

### 6.4 Reference to other sections

Reference to other sections Safe handling: see section 7 Personal protection equipment: see section 8

## SECTION 7: Handling and storage



### 7.1 Precautions for safe handling

#### Protective measures

##### Specific requirements or handling rules

Do not breathe dust. Do not breathe gas/fumes/vapour/spray. See section 8.

##### Advices on general occupational hygiene

Normal precautions taken when handling chemicals should be observed.

### 7.2 Conditions for safe storage, including any incompatibilities

Only use containers specifically approved for the substance/product.

#### Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place. Protect against UV-radiation/sunlight Humidity.

#### Hints on joint storage

Storage class : 13

Storage class (TRGS 510) : 13

#### Keep away from

Store at least 3 metres apart from: Chemicals/products that react together readily

#### Further information on storage conditions

Keep container tightly closed and in a well-ventilated place.

### 7.3 Specific end use(s)

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : REPAR TIX SPEEDY HP  
Revision date : 28.04.2017  
Print date : 28.04.2017

Version (Revision) : 2.0.0 (1.0.0)

None

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### DNEL/DMEL and PNEC values

##### DNEL/DMEL

Limit value type : DNEL worker (local) ( CEMENT, PORTLAND, CHEMICALS ; CAS No. : 65997-15-1 )  
Exposure route : Inhalation  
Exposure frequency : Short-term (acute)  
Limit value : 1 mg/m<sup>3</sup>

### 8.2 Exposure controls

#### Appropriate engineering controls

If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

#### Personal protection equipment



When using do not eat, drink, smoke, sniff.

#### Eye/face protection

##### Suitable eye protection

Eye glasses with side protection DIN EN 166

#### Skin protection

##### Hand protection

Tested protective gloves must be worn DIN EN 374

#### Respiratory protection

Quarter-face mask (DIN EN 140) Half-face mask (DIN EN 140) Filtering Half-face mask (DIN EN 149)

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Safety relevant basis data

Aspect		powder
Colour		gray
Odour		none
Melting point/melting range :		No data available
Freezing point :		No data available
Vapour density	( air = 1 )	Data not available
Initial boiling point and boiling range :	( 1013 hPa )	No data available
Decomposition temperature :		No data available
Self flammability		not applicable
Flash point :		Not flammable
Ignition temperature :		No data available
Lower explosion limit :		No data available
Upper explosion limit :		No data available
Explosive properties :		No data available.
Explosive properties		Not applicable
Vapour pressure	( 20 °C )	negligible
Density :	( 20 °C )	No data available

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : REPAR TIX SPEEDY HP  
Revision date : 28.04.2017  
Print date : 28.04.2017

Version (Revision) : 2.0.0 (1.0.0)

Relative density :	( 20 °C )	No data available
Water solubility :	( 20 °C )	almost insoluble
pH :	>	11
Log Pow	( 20 °C )	not applicable
Viscosity :	( 20 °C )	No data available
Odour threshold :		No data available
Relative vapour density :	( 20 °C )	No data available
Evaporation rate :		No data available
Maximum VOC content (EC) :		0 Wt %
Oxidizing properties		Not oxidising

### 9.2 Other information

None

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Basic reaction when in mixed with water before to became a solid inert compound.

### 10.2 Chemical stability

Stable under recommended storage and handling conditions. See section 7. No additional measures necessary.

### 10.3 Possibility of hazardous reactions

No hazardous reactions when stored and handled properly.

### 10.4 Conditions to avoid

Protect from contact with water to avoid solidification of the product.

### 10.5 Incompatible materials

Acid

### 10.6 Hazardous decomposition products

None

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute effects

##### Acute oral toxicity

It has no significant toxicity properties.

##### Acute dermal toxicity

Parameter :	LD50 ( CEMENT, PORTLAND, CHEMICALS ; CAS No. : 65997-15-1 )
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	> 2000 mg/kg bw/day
Exposure time :	24 days

It has no significant toxicity properties.

#### Irritant and corrosive effects

##### Primary irritation to the skin

On contact with moist skin may cause thickening, cracking and cracking of the skin. Prolonged contact in combination with existing abrasions can cause burns.

##### Irritation to eyes

Direct contact with the product may cause corneal injury due to mechanical stress, immediate or delayed irritation or inflammation. The direct contact with large quantities of product dry or with projections of wet product can cause effects ranging from irritation ocular moderate (eg. Conjunctivitis or blepharitis) to chemical burns and blindness.

##### Irritation to respiratory tract

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : REPAR TIX SPEEDY HP  
Revision date : 28.04.2017  
Print date : 28.04.2017

Version (Revision) : 2.0.0 (1.0.0)

Dust may irritate throat and respiratory system. Coughing, sneezing and panting may occur as a result of exposure above the occupational exposure limits.

### Sensitisation

Eczema can be developed as a result of exposure to dust damp, caused both by the high pH which induces irritant contact dermatitis after prolonged contact, either by an immunological reaction to Cr (VI) soluble which causes allergic contact dermatitis.

#### In case of inhalation

not sensitising.

### Repeated dose toxicity (subacute, subchronic, chronic)

#### Subacute inhalation toxicity

The available evidence indicates clearly that occupational exposure to cement dust content in the product causes deficits in lung function. However, the evidence available at present are insufficient to establish with certainty the dose-response relationship for these effects.

#### Chronic inhalation toxicity

There were no chronic effects or effects at low concentrations.

### CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

The ingredients in this mixture do not meet the criteria for classification as CMR according to CLP.

## SECTION 12: Ecological information

Do not allow uncontrolled discharge of product into the environment.

### 12.1 Toxicity

No information available.

### 12.2 Persistence and degradability

Poorly watersoluble, inorganic product. Can be mechanically precipitated to a large extent in biological sewage plants.

### 12.3 Bioaccumulative potential

not applicable

### 12.4 Mobility in soil

Low solubility in soil.

### 12.5 Results of PBT and vPvB assessment

This product is none, or does not contain a substance called a PBT or vPvB

### 12.6 Other adverse effects

No information available.

### 12.7 Additional ecotoxicological information

None

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product/Packaging disposal

Dispose according to legislation.

## SECTION 14: Transport information

### 14.1 UN number

No dangerous goods in sense of this transport regulation.

### 14.2 UN proper shipping name

No dangerous goods in sense of this transport regulation.

### 14.3 Transport hazard class(es)

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : REPAR TIX SPEEDY HP  
Revision date : 28.04.2017  
Print date : 28.04.2017

Version (Revision) : 2.0.0 (1.0.0)

No dangerous goods in sense of this transport regulation.

#### 14.4 Packing group

No dangerous goods in sense of this transport regulation.

#### 14.5 Environmental hazards

No dangerous goods in sense of this transport regulation.

#### 14.6 Special precautions for user

None

#### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU legislation

Regulation (EC) 1907/2006/CE (REACH). Regulation (EC) No 1272/2008 (CLP). Regulation (EU) 2015/830 requirements for the compilation of safety data sheets. Commission Regulation (EC) No 790/2009/CE (amending, for the purposes of its adaptation to technical and scientific progress (ATP), Regulation (EC) No 1272/2008). Commission Regulation (EU) No 286/2011 (amending, for the purposes of its adaptation to technical and scientific progress (ATP), Regulation (EC) No 1272/2008). Commission Regulation (EU) No 618/2012 (amending, for the purposes of its adaptation to technical and scientific progress (ATP), Regulation (EC) No 1272/2008). Commission Regulation (EU) No 487/2013 (amending, for the purposes of its adaptation to technical and scientific progress (ATP), Regulation (EC) No 1272/2008). Commission Regulation (EU) No 758/2013 (amending, for the purposes of its adaptation to technical and scientific progress (ATP), Regulation (EC) No 1272/2008). Commission Regulation (EU) No 944/2013 (amending, for the purposes of its adaptation to technical and scientific progress (ATP), Regulation (EC) No 1272/2008). Commission Regulation (EU) No 605/2014 (amending, for the purposes of its adaptation to technical and scientific progress (ATP), Regulation (EC) No 1272/2008). Commission Regulation (EU) No 1297/2015 (amending, for the purposes of its adaptation to technical and scientific progress (ATP), Regulation (EC) No 1272/2008).

##### Other regulations (EU)

**Regulation (CE) 1907/2006: Substance of very high concern included in the SVHC Candidate List**

None

##### National regulations

Italy: Legislative Decree 81/2008 (Consolidated Law on protection of health and safety at work), as amended and Directive 2009/161/UE - chemical risk assessment in accordance with Title IX

##### Water hazard class (WGK)

Class : nwg (Non-hazardous to water) Classification according to VwVwS

#### 15.2 Chemical Safety Assessment

not applicable

### SECTION 16: Other information

#### 16.1 Indication of changes

04. Most important symptoms and effects, both acute and delayed · 15. EU legislation

#### 16.2 Abbreviations and acronyms

##### LEGENDA:

ADR:	Accord européen relative au transport international des marchandises dangereuses par route (accordo europeo relativo al trasporto internazionale delle merci pericolose su strada)
ASTM:	ASTM International, originariamente nota come American Society for Testing and Materials (ASTM)
EINECS:	European Inventory of Existing Commercial Chemical Substances (Registro Europeo delle Sostanze chimiche in Commercio)
EC(0/50/100):	Effective Concentration 0/50/100 (Concentrazione Effettiva Massima per 0/50/100% degli Individui)
LC(0/50/100):	Lethal Concentration 0/50/100 (Concentrazione Letale per 0/50/100% degli Individui)

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : REPAR TIX SPEEDY HP  
Revision date : 28.04.2017  
Print date : 28.04.2017

Version (Revision) : 2.0.0 (1.0.0)

IC50:	Inhibitor Concentration 50 (Concentrazione Inibente per il 50% degli Individui)
NOEL:	No Observed Effect Level (Dose massima senza effetti)
NOEC:	No Observed Effect Concentration (Concentrazione massima senza effetti)
LOEC:	Lowest Observed Effect Concentration (Concentrazione massima alla quale è possibile evidenziare un effetto)
DNEL:	Derived No Effect Level (Dose derivata di non effetto)
DMEL:	Derived Minimum Effect Level (Dose derivata di minimo effetto)
CLP:	Classification, Labelling and Packaging (Classificazione, Etichettatura e Imballaggio)
CSR:	Rapporto sulla Sicurezza Chimica (Chemical Safety Report)
LD(0/50/100):	Lethal Dose 0/50/100 (Dose Letale per 0/50/100% degli Individui)
IATA:	International Air Transport Association (Associazione Internazionale del Trasporto Aereo)
ICAO:	International Civil Aviation Organization (Organizzazione Internazionale dell'Aviazione Civile)
Codice IMDG:	International Maritime Dangerous Goods code (Codice sul Regolamento del Trasporto Marittimo)
PBT:	Persistent, bioaccumulative and toxic (sostanze persistenti bioaccumulabili e tossiche)
RID:	Règlement concernent le transport International ferroviaire des marchandises Dangereuses (Regolamento concernente il trasporto Internazionale ferroviario delle merci Pericolose)
STEL:	Short term exposure limit (limite di esposizione a breve termine)
TLV:	Threshold limit value (soglia di valore limite)
TWA:	Time Weighted Average (media ponderata nel tempo)
UE:	Unione Europea
vPvB:	Very persistent very bioaccumulative (sostanze molto persistenti e molto bioaccumulabili)
N.D.:	Non disponibile.
N.A.:	Non applicabile
VwVwS.:	Text of Administrative Regulation on the Classification of Substances hazardous to waters into Water Hazard Classes (Verwaltungsvorschrift wassergefährdende Stoffe – VwVwS)
PNEC:	Predicted No Effect Concentration
PNOS:	Particulates not Otherwise Specified
BOD:	Biochemical Oxygen Demand
COD:	Chemical Oxygen Demand
BCF:	BioConcentration Factor
TRGS :	Technische Regeln für Gefahrstoffe -Technical Rules for Hazardous Substances, defined by The Federal Institute for Occupational Safety and Health, Germany
LCLo:	Lethal Concentration Low (La minima concentrazione letale)
ThOD:	Theoretical Oxygen Demand

### 16.3 Key literature references and sources for data

None

### 16.4 Classification for mixtures and used evaluation method according to regulation (EC) 1272/2008 [CLP]

calculated.

### 16.5 Relevant H- and EUH-phrases (Number and full text)

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.

### 16.6 Training advice

None

### 16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** REPAR TIX SPEEDY HP  
**Revision date :** 28.04.2017  
**Print date :** 28.04.2017

**Version (Revision) :** 2.0.0 (1.0.0)

---

the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---