

 Trade name :
 CONSILEX ST

 Revision date :
 11.05.2017

 Print date :
 31.05.2017

Version (Revision): 2.0.0 (1.0.0)

Safety Data Sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name CONSILEX ST Chemical name and synonym CONSILEX ST

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use WATERPROOFING

1.3. Details of the supplier of the safety data sheet

Name Azichem s.r.l.
Full address Via Gentile, 16/A
District and Country 46044 Goito (MNI)

Italia

tel. 0376 604185 fax 0376 604398

e-mail address of the competent person

responsible for the Safety Data Sheet info@azichem.com

1.4. Emergency telephone number

For urgent inquiries refer to CENTRO ANTIVELENI NIGUARDA MILANO 02.66101029

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 2
Eye irritation, category 2
H319
Specific target organ toxicity - single exposure, category 3
H225
H319
Causes serious eye irritation.
May cause drowsiness or dizziness.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



 Trade name :
 CONSILEX ST

 Revision date :
 11.05.2017
 Version (Revision) :
 2.0.0 (1.0.0)

 Print date :
 31.05.2017





Signal words: Danger

Hazard statements:

H225Highly flammable liquid and vapour.H319Causes serious eye irritation.H336May cause drowsiness or dizziness.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P261 Avoid breathing dust / fume / gas / mist / vapours / spray.

P280 Wear protective gloves/ protective clothing / eye protection / face protection.

P312 Call a POISON CENTRE / doctor / . . . if you feel unwell.

P370+P378 In case of fire: use . . . to extinguish.

Contains: PROPAN-2-OL

ETHYL ACETATE

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification x = Conc. % Classification 1272/2008 (CLP)

PROPAN-2-OL

CAS 67-63-0 $20 \le x < 30$ Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336

EC 200-661-7

INDEX 603-117-00-0 Reg. no. 01-2119457558-25

ETHYL SILICATE

CAS 78-10-4 10 ≤ x < 15 Flam. Liq. 3 H226, Acute Tox. 4 H332, Eye Irrit. 2 H319, STOT SE 3 H335

EC 201-083-8



Trade name : CONSILEX ST

Revision date : 11.05.2017 **Version (Revision) :** 2.0.0 (1.0.0)

Print date : 31.05.2017

INDEX 014-005-00-0

Reg. no. 01-2119496195-28

ETHYL ACETATE

CAS 141-78-6 0,5 ≤ x < 5 Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066

EC 205-500-4

INDEX 607-022-00-5

Reg. no. 01-2119475103-46

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS



 Trade name :
 CONSILEX ST

 Revision date :
 11.05.2017

 Print date :
 31.05.2017

Version (Revision): 2.0.0 (1.0.0)

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection



CONSILEX ST Trade name : Revision date : 11.05.2017 Print date : 31.05.2017

Version (Revision): 2.0.0 (1.0.0)

8.1. Control parameters

Regulatory References:

DEU Deutschland GBR United Kingdom TRGS 900 (Fassung 31.1.2018 ber.) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte

EH40/2005 Workplace exposure limits Monitorul Oficial al României 44; 2012-01-19 România

ROU EU OEL EU Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive

2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC. ACGIH 2018

TLV-ACGIH

PROPAN-2-OL Threshold Limit Value								
Type	Country	TW A/8h		STEL/15min				
<u>"</u>	<u> </u>	mg/m3	ppm	mg/m3	ppm			
AGW	DEU	500	200	1000	400			
MAK	DEU	500	200	1000	400			
WEL	GBR	999	400	1250	500			
TLV	ROU	200	81	500	203	SKIN		
TLV-ACGIH		492	200	983	400			
Predicted no-effect concentra	tion - PNEC							
Normal value in fresh water				140,9	mç	g/l		
Normal value in marine water				140,9	mç	g/l		
Normal value for water, interm	nittent release			149,9	mç	g/l		
Normal value for the food cha	in (secondary poisor	ning)		160	mç	g/kg		
Normal value for the terrestria	l compartment			28	mç	g/kg		
Health - Derived no-effect	ct level - DNEL / I	OMEL						
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	26 mg/kg/d				
Inhalation			VND	89 mg/m3			VND	500 mg/m3
Skin			VND	319 mg/kg/d			VND	888 mg/kg/d

ETHYL SILICATE								
Threshold Limit Value								
Туре	Country	TWA/8h		STEL/15min				
		mg/m3	ppm	mg/m3	ppm			
AGW	DEU	12	1,4	12	1,4			
MAK	DEU	86	10	86	10			
TLV	ROU	100		200				
OEL	EU	44	5					
TLV-ACGIH		85	10					

ETHYL ACETATE					
Threshold Limit Value					
Туре	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm



Trade name : CONSILEX ST

Revision date : 11.05.2017 **Version (Revision) :** 2.0.0 (1.0.0)

Print date : 31.05.2017

Normal value for the terrestrial compartment

AGW	DEU	1500	400	3000	800	
MAK	DEU	1500	400	3000	800	
WEL	GBR		200		400	
OEL	EU	734	200	1468	400	
TLV-ACGIH		1441	400			
Predicted no-effect conce	entration - PNEC					
Normal value in fresh wa	ter			0,24	mg/l	
Normal value in marine v	vater			0,024	mg/l	
Normal value for fresh w	ater sediment			1,15	mg/kg	
Normal value for marine	water sediment			0,115	mg/kg	
Normal value of STP mid	croorganisms			650	mg/l	

Health - Derived no-ef	fect level - DNEL / D	MEL						
	Effects on				Effects on			
	consumers				workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic	Acute local	Acute	Chronic local	Chronic
				systemic		systemic		systemic
Oral		VND	VND	4,5 mg/kg/d				
Inhalation	734 mg/m3	734 mg/m3	367 mg/m3	367 mg/m3	1468 mg/m3	1468 mg/m3	734 mg/m3	734 mg/m3
Skin			VND	37 mg/kg/d			VND	63 mg/kg/d

0,148

mg/kg/d

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).



Trade name : CONSILEX ST

Revision date : 11.05.2017 **Version (Revision) :** 2.0.0 (1.0.0)

Print date : 31.05.2017

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a type AX filter, whose limit of use will be defined by the manufacturer (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance liquid Colour colourless Odour characteristic Odour threshold Not available Not available Melting point / freezing point Not available Initial boiling point > 35 °C Not available Boiling range Flash point < 23 °C Not available **Evaporation Rate** Flammability of solids and gases Not available Lower inflammability limit Not available Upper inflammability limit Not available Lower explosive limit Not available Upper explosive limit Not available Vapour pressure Not available Vapour density Not available Relative density Not available Solubility insoluble Partition coefficient: n-octanol/water Not available Auto-ignition temperature Not available Not available Decomposition temperature Viscosity Not available Not available Explosive properties Oxidising properties Not available

9.2. Other information

VOC (Directive 2010/75/EC) : 43,62 % VOC (volatile carbon) : 24,10 %

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.



2.0.0 (1.0.0)

 Trade name :
 CONSILEX ST

 Revision date :
 11.05.2017
 Version (Revision) :

 Print date :
 31.05.2017

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:
> 20 mg/l
LD50 (Oral) of the mixture:
Not classified (no significant component)
LD50 (Dermal) of the mixture:
Not classified (no significant component)



 Trade name :
 CONSILEX ST

 Revision date :
 11.05.2017
 Version (Revision) :
 2.0.0 (1.0.0)

 Print date :
 31.05.2017

PROPAN-2-OL

LD50 (Oral) 4710 mg/kg Rat

LD50 (Dermal) 12800 mg/kg Rat

LC50 (Inhalation) 72,6 mg/l/4h Rat

ETHYL ACETATE

LD50 (Oral) 5620 mg/kg/bw rat

LD50 (Dermal) > 20000 mg/kg/bw rabbit

LC50 (Inhalation) > 6000 ppm

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD



CONSILEX ST Trade name : Revision date: 11.05.2017

Version (Revision): 2.0.0 (1.0.0) Print date : 31.05.2017

Does not meet the classification criteria for this hazard class

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

PROPAN-2-OL

LC50 - for Fish 9640 mg/l/96h EC50 - for Crustacea > 100 mg/l/48h EC50 - for Algae / Aquatic Plants > 100 mg/l/72h

ETHYL ACETATE

LC50 - for Fish > 212 mg/l/96h pesce

EC50 - for Crustacea > 150 mg/l/48h mexican axolot

12.2. Persistence and degradability

ETHYL SILICATE

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

PROPAN-2-OL Rapidly degradable

12.3. Bioaccumulative potential

ETHYL SILICATE

Partition coefficient: n-octanol/water 3,18 BCF 3,16

PROPAN-2-OL

Partition coefficient: n-octanol/water 0,05

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects



2.0.0 (1.0.0)

Version (Revision):

Trade name : CONSILEX ST Revision date: 11.05.2017 Print date :

31.05.2017

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number

ADR / RID, IMDG,

1993

IATA:

14.2. UN proper shipping name

ADR / RID: FLAMMABLE LIQUID, N.O.S. (PROPAN-2-OL; ETHYL ACETATE) IMDG: FLAMMABLE LIQUID, N.O.S. (PROPAN-2-OL; ETHYL ACETATE) FLAMMABLE LIQUID, N.O.S. (PROPAN-2-OL; ETHYL ACETATE) IATA:

14.3. Transport hazard class(es)

ADR / RID:

Class: 3

Label: 3

IMDG:

Class: 3

Label: 3

IATA:

Class: 3

Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA:

Ш

14.5. Environmental hazards

ADR / RID: NO IMDG: NO IATA: NO

Substances subject to the Stockholm Convention:

None



Trade name : Revision date : Print date :	CONSILEX ST 11.05.2017 31.05.2017	Version (Revision) :	2.0.0 (1.0.0)
14.6. Special precautions for	user		
ADR / RID:	HIN - Kemler: 33	Limited Quantities: 1	Tunnel restriction
	Special Provision: 640C	L	code: (D/E)
IMDG:	EMS: F-E, <u>S-E</u>	Limited Quantities: 1	
IATA:	Cargo:	L Maximum quantity: 60 L	Packaging instructions:
	Pass.:	Maximum quantity: 5 L	364 Packaging instructions: 353
	Special Instructions:	А3	333
SECTION 15. Regula		the substance or mixture	
15.1. Safety, health and env	ironmental regulations/legislation specific for t	the substance or mixture	
Seveso Category - Directive 20	12/18/EC: P5c		
Restrictions relating to the prod	uct or contained substances pursuant to Annex X\	/II to EC Regulation 1907/2006	
Product Point	3 - 40		
Substances in Candidate List (Art. 59 REACH)		
On the basis of available data,	the product does not contain any SVHC in percent	age greater than 0,1%.	
Substances subject to authoris	ation (Annex XIV REACH)		
None			
Substances subject to exportat	ion reporting pursuant to (EC) Reg. 649/2012:		
None			
Substances subject to the Rotte	erdam Convention:		



Trade name : CONSILEX ST

Revision date : 11.05.2017 **Version (Revision) :** 2.0.0 (1.0.0)

Print date : 31.05.2017

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2 Flammable liquid, category 2
Flam. Liq. 3 Flammable liquid, category 3
Acute Tox. 4 Acute toxicity, category 4
Eye Irrit. 2 Eye irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

H225 Highly flammable liquid and vapour.H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds



Trade name : CONSILEX ST Revision date: 11.05.2017

Version (Revision): 2.0.0 (1.0.0) Print date : 31.05.2017

vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation

- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EÚ) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- The Merck Index. 10th Edition Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 04 / 06 / 07 / 08 / 11 / 12 / 14 / 15.