

Scheda di dati di sicurezza

conforme Regolamento (CE) n. 1907/2006 (REACH)



Nome commerciale del prodotto : SYNTECH GROUT EP Comp. A
Data di redazione : 19.02.2021
Data di stampa : 19.02.2021

Versione : 1.0.0

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

SYNTECH GROUT EP Comp. A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Building and construction preparations: Two-component castable epoxy mortar for repairs and anchors

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

AZICHEM Srl

Street : Via G. Gentile16/A

Postal code/city : 46044 Goito (MN)

Telephone : +390376604185/604365

Telefax : +39 0376 604398

Information contact : info@azichem.com

1.4 Emergency telephone number

Centro Antiveleni di Milano 02 66101029 (CAV Ospedale Niguarda Ca' Granda -Milano) (24h)

Centro Antiveleni di Pavia 0382 24444 (CAV IRCCS Fondazione Maugeri - Pavia)

Centro Antiveleni di Bergamo 800 883300 (CAV Ospedali Riuniti - Bergamo)

Centro Antiveleni di Firenze 055 7947819 (CAV Ospedale Careggi - Firenze)

Centro Antiveleni di Roma 06 3054343 (CAV Policlinico Gemelli - Roma)

Centro Antiveleni di Roma 06 49978000 (CAV Policlinico Umberto I - Roma) Centro Antiveleni di Napoli 081 7472870 (CAV Ospedale Cardarelli - Napoli)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Aquatic Chronic 2 ; H411 - Hazardous to the aquatic environment : Chronic 2 ; Toxic to aquatic life with long lasting effects.

Eye Irrit. 2 ; H319 - Serious eye damage/eye irritation : Category 2 ; Causes serious eye irritation.

Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.

Skin Sens. 1 ; H317 - Skin sensitisation : Category 1 ; May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Health hazard (GHS08) · Environment (GHS09) · Exclamation mark (GHS07)

Signal word

Danger

Hazard components for labelling

REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6

POLY[(PHENYL GLYCIDYL ETHER)-CO-FORMALDEHYDE] ; CAS No. : 28064-14-4

Scheda di dati di sicurezza

conforme Regolamento (CE) n. 1907/2006 (REACH)



Nome commerciale del prodotto : SYNTECH GROUT EP Comp. A
Data di redazione : 19.02.2021
Data di stampa : 19.02.2021

Versione : 1.0.0

OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL] DERVIVS ; CAS No. : 68609-97-2

Hazard statements

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P302+P352 IF ON SKIN: Wash with plenty of water
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P501 Dispose of contents/container in accordance with local regulation

Special rules for supplemental label elements for certain mixtures

EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

QUARTZ (SiO₂) ; EC No. : 238-878-4; CAS No. : 14808-60-7

Weight fraction : ≥ 35 - < 40 %
Classification 1272/2008 [CLP] : STOT RE 1 ; H372

REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700) ; CAS No. : 25068-38-6

Weight fraction : ≥ 20 - < 25 %
Classification 1272/2008 [CLP] : Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 Eye Irrit. 2 ; H319 Aquatic Chronic 2 ; H411

POLY[(PHENYL GLYCIDYL ETHER)-CO-FORMALDEHYDE] ; CAS No. : 28064-14-4

Weight fraction : ≥ 5 - < 10 %
Classification 1272/2008 [CLP] : Skin Sens. 1 ; H317 Aquatic Chronic 2 ; H411

OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL] DERVIVS ; REACH registration No. : 01 2119485289-22 ; EC No. : 271-846-8; CAS No. : 68609-97-2

Weight fraction : ≥ 5 - < 10 %
Classification 1272/2008 [CLP] : Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317

BENZYL ALCOHOL ; REACH registration No. : 01-2119492630-38 ; EC No. : 202-859-9; CAS No. : 100-51-6

Weight fraction : ≥ 1 - < 5 %
Classification 1272/2008 [CLP] : Acute Tox. 4 ; H302 Acute Tox. 4 ; H332 Eye Irrit. 2 ; H319

Additional information

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

When in doubt or if symptoms are observed, get medical advice.

Following inhalation

Scheda di dati di sicurezza

conforme Regolamento (CE) n. 1907/2006 (REACH)



Nome commerciale del prodotto : SYNTECH GROUT EP Comp. A
Data di redazione : 19.02.2021
Data di stampa : 19.02.2021

Versione : 1.0.0

Remove victim out of the danger area. Symptoms may develop several hours following exposure; medical observation therefore necessary for at least 48 hours.

In case of skin contact

Wash immediately with: Water Remove contaminated, saturated clothing immediately. In case of skin irritation, consult a physician. In case of skin reactions, consult a physician.

After eye contact

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Never give anything by mouth to an unconscious person or a person with cramps.

4.2 Most important symptoms and effects, both acute and delayed

Irritation to eyes May cause an allergic skin reaction. Primary irritation to the skin

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Extinguishing powder alcohol resistant foam Carbon dioxide (CO₂) Water mist

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Carbon monoxide.

5.3 Advice for firefighters

Remove persons to safety.

Special protective equipment for firefighters

Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Clear spills immediately. Wear a self-contained breathing apparatus and chemical protective clothing.

For non-emergency personnel

Remove persons to safety.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3 Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal.

For cleaning up

The contaminated area should be cleaned up immediately with: Water Retain contaminated washing water and dispose it.

6.4 Reference to other sections

Reference to other sections Safe handling: see section 7 Personal protection equipment: see section 8

SECTION 7: Handling and storage

Scheda di dati di sicurezza

conforme Regolamento (CE) n. 1907/2006 (REACH)



Nome commerciale del prodotto : SYNTECH GROUT EP Comp. A
Data di redazione : 19.02.2021
Data di stampa : 19.02.2021

Versione : 1.0.0



7.1 Precautions for safe handling

Protective measures

Specific requirements or handling rules

Do not breathe dust. Do not breathe gas/fumes/vapour/spray. See section 8.

Advices on general occupational hygiene

Normal precautions taken when handling chemicals should be observed.

7.2 Conditions for safe storage, including any incompatibilities

Only use containers specifically approved for the substance/product.

Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place. Protect against UV-radiation/sunlight Humidity.

Hints on joint storage

Storage class : 10

Storage class (TRGS 510) : 6.1C

Keep away from

Store at least 3 metres apart from: Chemicals/products that react together readily

Further information on storage conditions

Keep container tightly closed and in a well-ventilated place.

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

DNEL/DMEL and PNEC values

DNEL/DMEL

Limit value type : DNEL Consumer (systemic) (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6)

Exposure route : Dermal

Exposure frequency : Short-term (acute)

Limit value : 3,571 mg/kg bw/day

Limit value type : DNEL Consumer (systemic) (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6)

Exposure route : Oral

Exposure frequency : Short-term (acute)

Limit value : 0,75 mg/kg bw/day

Limit value type : DNEL Consumer (systemic) (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6)

Exposure route : Dermal

Exposure frequency : Long-term (repeated)

Limit value : 3,571 mg/kg bw/day

Limit value type : DNEL Consumer (systemic) (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6)

Scheda di dati di sicurezza

conforme Regolamento (CE) n. 1907/2006 (REACH)



Nome commerciale del prodotto : SYNTECH GROUT EP Comp. A
Data di redazione : 19.02.2021
Data di stampa : 19.02.2021

Versione : 1.0.0

Exposure route :	Oral
Exposure frequency :	Long-term (repeated)
Limit value :	0,75 mg/kg bw/day
Limit value type :	DNEL worker (systemic) (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6)
Exposure route :	Dermal
Exposure frequency :	Short-term (acute)
Limit value :	8,33 mg/kg bw/day
Limit value type :	DNEL worker (systemic) (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6)
Exposure route :	Inhalation
Exposure frequency :	Short-term (acute)
Limit value :	12,25 mg/m ³
Limit value type :	DNEL worker (systemic) (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6)
Exposure route :	Dermal
Exposure frequency :	Long-term (repeated)
Limit value :	8,33 mg/kg bw/day
Limit value type :	DNEL worker (systemic) (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6)
Exposure route :	Inhalation
Exposure frequency :	Long-term (repeated)
Limit value :	12,25 mg/m ³
Limit value type :	DNEL Consumer (systemic) (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Exposure route :	Dermal
Exposure frequency :	Short-term (acute)
Limit value :	28,5 mg/kg
Limit value type :	DNEL Consumer (systemic) (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Exposure route :	Inhalation
Exposure frequency :	Short-term (acute)
Limit value :	40,55 mg/m ³
Limit value type :	DNEL Consumer (systemic) (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Exposure route :	Oral
Exposure frequency :	Short-term (acute)
Limit value :	25 mg/kg
Limit value type :	DNEL Consumer (systemic) (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Exposure route :	Dermal
Exposure frequency :	Long-term (repeated)
Limit value :	5,7 mg/kg
Limit value type :	DNEL worker (local) (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Exposure route :	Dermal
Exposure frequency :	Short-term (acute)
Limit value :	47 mg/kg
Limit value type :	DNEL worker (systemic) (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Exposure route :	Inhalation
Exposure frequency :	Short-term (acute)
Limit value :	450 mg/m ³
Limit value type :	DNEL worker (systemic) (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Exposure route :	Dermal
Exposure frequency :	Long-term (repeated)
Limit value :	9,5 mg/kg

Scheda di dati di sicurezza

conforme Regolamento (CE) n. 1907/2006 (REACH)



Nome commerciale del prodotto : SYNTECH GROUT EP Comp. A
Data di redazione : 19.02.2021
Data di stampa : 19.02.2021

Versione : 1.0.0

Limit value type :	DNEL worker (systemic) (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Exposure route :	Inhalation
Exposure frequency :	Long-term (repeated)
Limit value :	90 mg/m ³
PNEC	
Limit value type :	PNEC aquatic, freshwater (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6)
Limit value :	6 µg/l
Limit value type :	PNEC aquatic, intermittent release (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6)
Limit value :	18 µg/l
Limit value type :	PNEC aquatic, marine water (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6)
Limit value :	0,6 µg/l
Limit value type :	PNEC sediment, freshwater (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6)
Limit value :	0,96 mg/kg
Limit value type :	PNEC sediment, marine water (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6)
Limit value :	0,096 mg/kg
Limit value type :	PNEC Soil (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6)
Limit value :	0,196 mg/kg
Limit value type :	PNEC Secondary Poisoning (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6)
Limit value :	11 mg/kg
Limit value type :	PNEC sewage treatment plant (STP) (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6)
Limit value :	10 mg/l
Limit value type :	PNEC aquatic, freshwater (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Limit value :	1 mg/l
Limit value type :	PNEC aquatic, intermittent release (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Limit value :	2,3 mg/l
Limit value type :	PNEC aquatic, marine water (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Limit value :	0,1 mg/l
Limit value type :	PNEC sediment, freshwater (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Limit value :	5,27 mg/kg
Limit value type :	PNEC sediment, marine water (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Limit value :	0,52 mg/kg
Limit value type :	PNEC Soil (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Limit value :	0,45 mg/kg
Limit value type :	PNEC sewage treatment plant (STP) (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Limit value :	39 mg/l

8.2 Exposure controls

Appropriate engineering controls

If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Personal protection equipment

Scheda di dati di sicurezza

conforme Regolamento (CE) n. 1907/2006 (REACH)



Nome commerciale del prodotto : SYNTECH GROUT EP Comp. A
Data di redazione : 19.02.2021
Data di stampa : 19.02.2021

Versione : 1.0.0



When using do not eat, drink, smoke, sniff.

Eye/face protection

Suitable eye protection

Safety glasses with side shields (EN 166).

Skin protection

Hand protection

Wear rubber gloves approved under standard EN374.

Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values

Suitable respiratory protection apparatus

Full-/half-/quarter-face masks (DIN EN 136/140) Filter type: A

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Safety relevant basis data

Aspect			syrupe liquid
Colour			different colors
Odour			none
Melting point/melting range :	(1013 hPa)		-10 °C
Vapour density	(air = 1)		Not Determined
Initial boiling point and boiling range :	(1013 hPa)	>	150 °C
Decomposition temperature :			400 °C
Flash point :			150 °C
Ignition temperature :			380 °C
Flammability (solid, gas)			Data not available
Lower explosion limit :			not determined
Upper explosion limit :			not determined
Explosive properties			Product is not explosive
Vapour pressure	(20 °C)		not determined
Density :	(20 °C)		1,6 g/cm ³
Water solubility :	(20 °C)		insoluble
Soluble in:	(20 °C)		organic solvents
pH :			not determined
Log Pow	(20 °C)		not applicable
Viscosity :	(20 °C)		25000 mPa.s
Odour threshold :			not determined
Evaporation rate :			not determined
Oxidizing properties			Not oxidising

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

Scheda di dati di sicurezza

conforme Regolamento (CE) n. 1907/2006 (REACH)



Nome commerciale del prodotto : SYNTECH GROUT EP Comp. A
Data di redazione : 19.02.2021
Data di stampa : 19.02.2021

Versione : 1.0.0

Decomposes on heating. See section 7. No additional measures necessary.

10.3 Possibility of hazardous reactions

None particular

10.4 Conditions to avoid

Do not expose this product to high temperatures.

10.5 Incompatible materials

May react violently with strong acids. Oxidizing agents. Strong bases.

10.6 Hazardous decomposition products

Carbon monoxide.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute effects

Acute oral toxicity

Parameter :	LD50 (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6)
Exposure route :	Oral
Species :	Rat
Effective dose :	> 2000 mg/kg
Parameter :	LD50 (OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL] DERIVS ; CAS No. : 68609-97-2)
Exposure route :	Oral
Species :	Rat
Effective dose :	17100 mg/kg
Parameter :	LD50 (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Exposure route :	Oral
Species :	Rat
Effective dose :	1620 mg/kg

Acute dermal toxicity

Parameter :	LD50 (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6)
Exposure route :	Dermal
Species :	Rat
Effective dose :	> 2000 mg/kg
Parameter :	LD50 (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	2000 mg/kg

Acute inhalation toxicity

Parameter :	LC50 (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Exposure route :	Inhalation
Species :	Rat
Effective dose :	> 4178 mg/l
Exposure time :	4 h

Irritant and corrosive effects

Primary irritation to the skin

Irritant.

Irritation to eyes

Irritant.

Irritation to respiratory tract

Not an irritant.

Scheda di dati di sicurezza

conforme Regolamento (CE) n. 1907/2006 (REACH)



Nome commerciale del prodotto : SYNTECH GROUT EP Comp. A
Data di redazione : 19.02.2021
Data di stampa : 19.02.2021

Versione : 1.0.0

Sensitisation

In case of skin contact

sensitising.

In case of inhalation

not sensitising.

Repeated dose toxicity (subacute, subchronic, chronic)

There were no chronic effects or effects at low concentrations.

Subacute oral toxicity

Parameter : NOAEL(C) (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Exposure route : Oral
Species : Rat
Effective dose : 400 mg/kg

Subacute inhalation toxicity

Parameter : NOAEL(C) (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Exposure route : Inhalation
Species : Rat
Effective dose : 1072 mg/m³
Method : OECD 412

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

The ingredients in this mixture do not meet the criteria for classification as CMR according to CLP.

Reproductive toxicity

Adverse effects on sexual function and fertility

Parameter : NOAEL(C) (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Exposure route : Rat
Effective dose : 1072 mg/m³

SECTION 12: Ecological information

Do not allow uncontrolled discharge of product into the environment.

12.1 Toxicity

Aquatic toxicity

Acute (short-term) fish toxicity

Parameter : LC50 (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6)
Species : Oncorhynchus mykiss (Rainbow trout)
Effective dose : 1,2 - 2,3 mg/l
Exposure time : 96 h
Method : OECD 203

Parameter : LC50 (OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL] DERIVS ; CAS No. : 68609-97-2)
Effective dose : > 1000 mg/l
Exposure time : 96 h

Parameter : LC50 (POLY[(PHENYL GLYCIDYL ETHER)-CO-FORMALDEHYDE] ; CAS No. : 28064-14-4)
Effective dose : > 1 mg/l
Exposure time : 96 h

Parameter : LC50 (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Species : Pimephales promelas (fathead minnow)
Effective dose : 770 mg/l
Exposure time : 1 h

Parameter : LC50 (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Species : Pimephales promelas (fathead minnow)

Scheda di dati di sicurezza

conforme Regolamento (CE) n. 1907/2006 (REACH)



Nome commerciale del prodotto : SYNTECH GROUT EP Comp. A
Data di redazione : 19.02.2021
Data di stampa : 19.02.2021

Versione : 1.0.0

Effective dose : 460 mg/l

Exposure time : 96 h

Chronic (long-term) fish toxicity

Parameter : NOEC (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6)

Species : Daphnia

Effective dose : 0,3 mg/l

Exposure time : 21 days

Method : OECD 211

Acute (short-term) daphnia toxicity

Parameter : EC50 (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6)

Species : Daphnia magna (Big water flea)

Effective dose : 1,1 - 2,8 mg/l

Exposure time : 48 h

Method : OECD 202

Parameter : EC50 (BENZYL ALCOHOL ; CAS No. : 100-51-6)

Species : Daphnia magna (Big water flea)

Effective dose : 230 mg/l

Exposure time : 48 h

Parameter : EC50 (BENZYL ALCOHOL ; CAS No. : 100-51-6)

Species : Daphnia magna (Big water flea)

Effective dose : 66 mg/l

Exposure time : 21 days

Method : OECD 211

Chronic (long-term) daphnia toxicity

Parameter : NOEC (BENZYL ALCOHOL ; CAS No. : 100-51-6)

Species : Daphnia magna (Big water flea)

Effective dose : 51 mg/l

Exposure time : 21 days

Method : OECD 211

Acute (short-term) algae toxicity

Parameter : EC50 (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6)

Species : Selenastrum capricornutum

Effective dose : 9,4 mg/l

Exposure time : 72 h

Parameter : EC50 (OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL] DERVIVS ; CAS No. : 68609-97-2)

Species : Pseudokirchneriella subcapitata

Effective dose : 843 mg/l

Exposure time : 72 h

Parameter : EC50 (BENZYL ALCOHOL ; CAS No. : 100-51-6)

Species : Pseudokirchneriella subcapitata

Effective dose : 770 mg/l

Exposure time : 72 h

Chronic (long-term) algae toxicity

Parameter : NOEC (OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL] DERVIVS ; CAS No. : 68609-97-2)

Species : Pseudokirchneriella subcapitata

Effective dose : 500 mg/l

Exposure time : 72 h

Bacteria toxicity

Parameter : IC50 (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6)

Scheda di dati di sicurezza

conforme Regolamento (CE) n. 1907/2006 (REACH)



Nome commerciale del prodotto : SYNTECH GROUT EP Comp. A
Data di redazione : 19.02.2021
Data di stampa : 19.02.2021

Versione : 1.0.0

Species : Activated sludge
Effective dose : 9,4 mg/l
Exposure time : 3 h
Parameter : EC50 (OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL] DERIVS ; CAS No. : 68609-97-2)
Species : Activated sludge
Effective dose : > 100 mg/l
Exposure time : 3 h

12.2 Persistence and degradability

Biodegradation

Parameter : Biodegradation (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6)
Effective dose : 5 %
Exposure time : 28 days
Method : OECD 301F/ ISO 9408/ EEC 92/69/V, C.4-D
Parameter : Biodegradation (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6)
Effective dose : 6 - 12 %
Exposure time : 28 days
Method : OECD 301B/ ISO 9439/ EEC 92/69/V, C.4-C
Parameter : Biodegradation (POLY[(PHENYL GLYCIDYL ETHER)-CO-FORMALDEHYDE] ; CAS No. : 28064-14-4)
Effective dose : 13 %
Exposure time : 96 h
Method : OECD 301B/ ISO 9439/ EEC 92/69/V, C.4-C
Parameter : Biodegradation (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Effective dose : 92 - 96 %
Exposure time : 14 days
Method : OECD 301C/ ISO 9408/ EEC 92/69/V, C.4-F
Parameter : DOC reduction (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Effective dose : 95 - 97 %
Exposure time : 21 days
Method : OECD 301A/ ISO 7827/ EEC 92/69/V, C.4-A

12.3 Bioaccumulative potential

Parameter : Bioconcentration factor (BCF) (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6)
Concentration : 3 - 31
Parameter : Partition coefficient n-octanol /water (log P O/W) (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6)
Concentration : > 2,918
Method : Regulation (EC) No. 440/2008, Annex, A.8

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

No information available.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

None

SECTION 13: Disposal considerations

Scheda di dati di sicurezza

conforme Regolamento (CE) n. 1907/2006 (REACH)



Nome commerciale del prodotto : SYNTECH GROUT EP Comp. A
Data di redazione : 19.02.2021
Data di stampa : 19.02.2021

Versione : 1.0.0

13.1 Waste treatment methods

Product/Packaging disposal

Dispose according to legislation.

SECTION 14: Transport information

14.1 UN number

UN 3082

14.2 UN proper shipping name

Land transport (ADR/RID)

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) · POLY[(PHENYL GLYCIDYL ETHER)-CO-FORMALDEHYDE])

Sea transport (IMDG)

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) · POLY[(PHENYL GLYCIDYL ETHER)-CO-FORMALDEHYDE])

Air transport (ICAO-TI / IATA-DGR)

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) · POLY[(PHENYL GLYCIDYL ETHER)-CO-FORMALDEHYDE])

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es) : 9
Classification code : M6
Hazard identification number (Kemler No.) : 90
Tunnel restriction code : E
Special provisions : LQ 5 I · E 1 · ADR : - (SP 375 <= 5 l/kg)
Hazard label(s) : 9 / N

Sea transport (IMDG)

Class(es) : 9
EmS-No. : F-A / S-F
Special provisions : LQ 5 I · E 1 · IMDG : - (SP 2.10.2.7 <= 5 l/kg)
Hazard label(s) : 9 / N

Air transport (ICAO-TI / IATA-DGR)

Class(es) : 9
Special provisions : E 1 · IATA : - (SP A197 <= 5 l/kg)
Hazard label(s) : 9 / N

14.4 Packing group

III

14.5 Environmental hazards

Land transport (ADR/RID) : Yes
Sea transport (IMDG) : Yes (P)
Air transport (ICAO-TI / IATA-DGR) : Yes

14.6 Special precautions for user

None

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

Scheda di dati di sicurezza

conforme Regolamento (CE) n. 1907/2006 (REACH)



Nome commerciale del prodotto : SYNTECH GROUT EP Comp. A
Data di redazione : 19.02.2021
Data di stampa : 19.02.2021

Versione : 1.0.0

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Regulation (EC) 1907/2006 (REACH).
Regulation (EC) No 1272/2008 (CLP).
Regulation (EU) 2015/830 requirements for the compilation of safety data sheets.
Amendings, for the purposes of its adaptation to technical and scientific progress, Regulation (EC) No 1272/2008: Commission Regulation (EC) No 790/2009 (I ATP). Commission Regulation (EU) No 286/2011(II ATP). Commission Regulation (EU) No 618/2012 (III ATP). Commission Regulation (EU) No 487/2013 (IV ATP). Commission Regulation (EU) No 944/2013 (V ATP). Commission Regulation (EU) No 605/2014 (VI ATP). Commission Regulation (EU) No 1297/2014 (VII ATP). Commission Regulation (EU) No 2015/1221 (VIII ATP). Commission Regulation (EU) No 2016/1179 (IX ATP). Commission Regulation 2017/776 (EU) No (X ATP). Regulation (EU) No 2018/669 (XI ATP). Regulation (EU) No 2018/669 (XI ATP). Regulation (EU) No 2018/669 (XI ATP).

Other regulations (EU)

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]
Classification according to Annex I, Part 1 E2 Hazardous to the aquatic environment in Category Chronic 2

Regulation (CE) 1907/2006: Substance of very high concern included in the SVHC Candidate List

None

National regulations

Italy: Legislative Decree 81/2008 (Consolidated Law on protection of health and safety at work), as amended and Directive 2009/161/UE - chemical risk assessment in accordance with Title IX

Water hazard class (WGK)

Class : 2 (Hazardous to water) Classification according to VwVwS

15.2 Chemical safety assessment

not applicable

SECTION 16: Other information

16.1 Indication of changes

None

16.2 Abbreviations and acronyms

LEGENDA:

ADR:	Accord européen relative au transport international des marchandises dangereuses par route (accordo europeo relativo al trasporto internazionale delle merci pericolose su strada)
ASTM:	ASTM International, originariamente nota come American Society for Testing and Materials (ASTM)
EINECS:	European Inventory of Existing Commercial Chemical Substances (Registro Europeo delle Sostanze chimiche in Commercio)
EC(0/50/100):	Effective Concentration 0/50/100 (Concentrazione Effettiva Massima per 0/50/100% degli Individui)
LC(0/50/100):	Lethal Concentration 0/50/100 (Concentrazione Letale per 0/50/100% degli Individui)
IC50:	Inhibitor Concentration 50 (Concentrazione Inibente per il 50% degli Individui)
NOEL:	No Observed Effect Level (Dose massima senza effetti)
NOEC:	No Observed Effect Concentration (Concentrazione massima senza effetti)
LOEC:	Lowest Observed Effect Concentration (Concentrazione massima alla quale è possibile evidenziare un effetto)
DNEL:	Derived No Effect Level (Dose derivata di non effetto)
DMEL:	Derived Minimum Effect Level (Dose derivata di minimo effetto)
CLP:	Classification, Labelling and Packaging (Classificazione, Etichettatura e Imballaggio)
CSR:	Rapporto sulla Sicurezza Chimica (Chemical Safety Report)
LD(0/50/100):	Lethal Dose 0/50/100 (Dose Letale per 0/50/100% degli Individui)
IATA:	International Air Transport Association (Associazione Internazionale del Trasporto Aereo)

Scheda di dati di sicurezza

conforme Regolamento (CE) n. 1907/2006 (REACH)



Nome commerciale del prodotto : SYNTECH GROUT EP Comp. A
Data di redazione : 19.02.2021
Data di stampa : 19.02.2021

Versione : 1.0.0

ICAO:	International Civil Aviation Organization (Organizzazione Internazionale dell'Aviazione Civile)
Codice IMDG:	International Maritime Dangerous Goods code (Codice sul Regolamento del Trasporto Marittimo)
PBT:	Persistent, bioaccumulative and toxic (sostanze persistenti bioaccumulabili e tossiche)
RID:	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regolamento concernente il trasporto Internazionale ferroviario delle merci Pericolose)
STEL:	Short term exposure limit (limite di esposizione a breve termine)
TLV:	Threshold limit value (soglia di valore limite)
TWA:	Time Weighted Average (media ponderata nel tempo)
UE:	Unione Europea
vPvB:	Very persistent very bioaccumulative (sostanze molto persistenti e molto bioaccumulabili)
N.D.:	Non disponibile.
N.A.:	Non applicabile
AwSV.:	Ordinance on facilities for handling substances that are hazardous to water (Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV))
PNEC:	Predicted No Effect Concentration
PNOS:	Particulates not Otherwise Specified
BOD:	Biochemical Oxygen Demand
COD:	Chemical Oxygen Demand
BCF:	BioConcentration Factor
TRGS :	Technische Regeln für Gefahrstoffe -Technical Rules for Hazardous Substances, defined by The Federal Institute for Occupational Safety and Health, Germany
LCLo:	Lethal Concentration Low (La minima concentrazione letale)
ThOD:	Theoretical Oxygen Demand

16.3 Key literature references and sources for data

None

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

calculated.

16.5 Relevant H- and EUH-phrases (Number and full text)

H302+H332	Harmful if swallowed or if inhaled.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.