



PRS.0102

PROTECH FLEX PRIMER

Primer specific for polyurethane sealants

Customs Code

3909 5090

Packaging

- Canister 1 kg

Application

- Brush

Family
Proseal

Type
Plastic and elasto-plastic sealants

Product Lines

- Aqua
- Building
- Infratech
- Floor

Functional Categories

- Transparent waterproofing of tiled terraces and balconies
- Osmotic waterproofing
- Waterproofing with hot-sprayed elastomeric coatings (100% pure polyurea)
- Waterproofing underground structures with hydro-expansive products
- Waterproofing control joints or construction joints
- Horizontal cement waterproofing of terraces and balconies
- Prefabrication
- Plastering and loose-fill of cracks and cavities on plasters and facades
- Elastomeric sealing of expansion and shrinkage joints on concrete floors and screeds

Components
Single-component

Appearance
Liquid

General description

A polyurethane bonding primer for preparing the subsequent filling of the joints with single-component polyurethane sealants in a cartridge (PROTECH FLEX or PROTECH SIGILFLEX MONO) or a two-component product (EG 91) on concrete and masonry surfaces.


Dosage


Approximately 0.02 kg of PROTECH FLEX PRIMER for every linear metre of joint to be treated.


Fields of application


Preliminary reinforcing impregnation of concrete surfaces, forming walls of flooring and roofing joints, prior to sealing it with polyurethane and epoxy-polyurethane sealants.

Basic features


 Density:
1 (± 0.01) kg/dm³


 Flammable material


 Pot-life:
60 min

 Shelf-life:
8 months

 Solvent-based product

 Temperature of use:
+5 / +35 °C

 Use wearing protective gloves

 Available colours
Amber

Technical specifications

Dry residue (10' a 150°C): 40 %

Viscosity (UNI 8701/3): 30 (± 5) mPa

IF YOU WANT TO SOLVE IT



www.azichem.com

Updated: 29/11/2021

General sales conditions and legal notices on

www.azichem.com/disclaimer

Tools cleansing

- Nitro thinner

Applicable on

- Plasters
- Concrete
- Cement-based or lime-based mortars
- Prefabricated concrete
- Drywall
- Wood
- Metal surfaces
- Plastic
- Fiber-cement
- Tiles
- Floor screed

Substrate preparation

The application surfaces should be clean, free of incrustations, crumbling and non-adhering parts, dust etc.

Instructions for use

Apply PROTECH FLEX PRIMER, using a brush with short bristles, on the walls of the joint to be sealed.

It is appropriate to provide for the insertion in the joint, whatever its nature and the specific foamed polyethylene kerb FILTENE FONDOGIUNTO, of the appropriate size for the joint to be sealed.

Storage and preservation

Protect from freezing. Store the product in its original packing, in a fresh and dry environment, avoiding frost and direct sunlight. Inadequate storage of the product may result in a loss of rheological performance. Store the product at a temperature between +5°C and +35°C.



Warnings, Precautions and Ecology

The general information, along with any instructions and recommendations for use of this product, including in this data sheet and eventually provided verbally or in writing, correspond to the present state of our scientific and practical knowledge.

Any technical and performance data reported is the result of laboratory tests conducted in a controlled environment and thus may be subject to modification in relation to the actual conditions of implementation.

Azichem Srl does not assume any liability arising from inadequate characteristics related to improper use of the product or connected to defects arising from factors or elements unrelated to the quality of the product, including improper storage.

Those wishing to utilise the product are required to determine prior to use whether or not the same is suitable for the intended use, assuming all consequent responsibility.

The technical and characteristic details contained in this data sheet shall be updated periodically. For consultation in real time, please visit the website: www.azichem.com. The date of revision is indicated in the space to the side. The current edition cancels out and replaces any previous version.

Please note that the user is required to read the latest Safety Data Sheet for this product, containing chemical-physical and toxicological data, risk phrases and other information regarding the safe transport, use and disposal of the product and its packaging. For consultation, please visit: www.azichem.com.

It is forbidden to dispose of the product and/or packaging in the environment.

Warning: it is a highly flammable material.

PROTECH FLEX PRIMER is produced/distributed by



Via Giovanni Gentile, 16/A - 46044 Goito (MN), Italy
info@azichem.com Tel. +39 0376.604185 /604365 Fax +39 0376 604398



www.azichem.com

Updated: **29/11/2021**
General sales conditions and legal
notices on
www.azichem.com/disclaimer