

PRT.0115

PROTECH TUNNEL

Tempera paint, high covering, for tunnels, galleries and subways

Customs Code

3209 1000

Packaging

- Pail 15 l

Application

- Low pressure airless nebulizer
- Brush
- Paint roller

Family
Protech

Product Lines
• **Infratech**

Components
Single-component

Type
Acrylic fixatives, paints and plasters

Functional Categories
• **Structural maintenance of tunnels**
• **Protective varnishing (painting)**

Appearance
Liquid

General description

Tempera paint with high specific coverage, high dry residue and discrete water repellence, for painting signs and decorative interior surfaces generally relating to tunnels, galleries, subways, etc.

Pure white: RAL 9010
Vermilion: RAL 2002


Dosage

Apply from 0.30 to 0.50 liters of PROTECH TUNNEL per square metre of surface to be painted.


Fields of application


Painting vertical and decorative signs for tunnels, galleries and subways.


Basic features

 Density:
1.56 g/cm³


 Nonflammable

 Shelf-life:
12 months

 Solvent-free

 Temperature of use:
+ 5 / +35 °C

 To be applied in two coats

 Available colours
Request available colors

Technical specifications

Alkali-resistant material

Complete hardening: 5-8 h

Dry residue: 68.73 %

Tools cleansing

- Water

Applicable on

- Concrete

Substrate preparation

The surfaces of application should be clean, free of any soiling, crumbling and non-adhering parts, or non-absorbent, dust, pre-existing paints, etc. Apply the specific fixative PROTECH FIX TUNNEL on the surfaces to be treated, using low pressure airless.

Instructions for use

Apply PROTECH TUNNEL with airless pumps at low pressure, diluting it preliminarily with water in the recommended percentage of 30%-40% by weight of the product.

IF YOU WANT TO SOLVE IT
 azichem

www.azichem.com

Updated: 24/08/2020

General sales conditions and legal notices on

www.azichem.com/disclaimer

Storage and preservation

Protect from freezing. Store the product in its original packing, in a fresh and dry environment, avoiding frost and direct sunlight. Inadequate storage of the product may result in a loss of rheological performance.



Warnings, Precautions and Ecology

The general information, along with any instructions and recommendations for use of this product, including in this data sheet and eventually provided verbally or in writing, correspond to the present state of our scientific and practical knowledge.

Any technical and performance data reported is the result of laboratory tests conducted in a controlled environment and thus may be subject to modification in relation to the actual conditions of implementation.

Azichem Srl does not assume any liability arising from inadequate characteristics related to improper use of the product or connected to defects arising from factors or elements unrelated to the quality of the product, including improper storage.

Those wishing to utilise the product are required to determine prior to use whether or not the same is suitable for the intended use, assuming all consequent responsibility.

The technical and characteristic details contained in this data sheet shall be updated periodically. For consultation in real time, please visit the website: www.azichem.com. The date of revision is indicated in the space to the side. The current edition cancels out and replaces any previous version.

Please note that the user is required to read the latest Safety Data Sheet for this product, containing chemical-physical and toxicological data, risk phrases and other information regarding the safe transport, use and disposal of the product and its packaging. For consultation, please visit: www.azichem.com.

It is forbidden to dispose of the product and/or packaging in the environment.

PROTECH TUNNEL is produced/distributed by



Via Giovanni Gentile, 16/A - 46044 Goito (MN), Italy
info@azichem.com Tel. +39 0376.604185 /604365 Fax +39 0376 604398



www.azichem.com

Updated: **24/08/2020**
General sales conditions and legal notices on www.azichem.com/disclaimer