

RDM.0220 **READYMESH**

MX-500

High performance 50mm steel fibres

Customs Code

7326 2000

Packaging

- Bag 20 kg

- Pallet: 50 x (Bag 20 kg)

Family Type

Readymesh Steel fibres for concrete

Product Lines Functional Cathegories

Infratech
 Improvement of mechanical and/or rheological
 Floor
 performance of newly manufactured mortars, plasters and

concretes

 Construction of high performance industrial concrete floors

• Prefabrication

Components Appearance

Single-component Fibers

Certifications and legislations



EN 14889-1:2006 (System 1)

Fibres for concrete - Steel fibres - Definitions, specification and conformity

General description

READYMESH MX-500 is a special carbon steel fibre, obtained by the extrusion and cutting of high-strength steel wire. Its special double-hooked form gives it a remarkable shear strength, thus conferring the concrete with excellent post-cracking structural strength even at low doses. READYMESH MX-500 significantly increases the mechanical performance of the structure in terms of toughness, ductility, fatigue, dynamic stress, shock, wear, tensile and shear strength and even post-cracking and damage behaviour.

Dosage

Variable according to the type of work to be carried out and/or performance to be achieved.

Fields of application

General preparation of fibre-reinforced concrete with high pre and post-cracking performance. Ideal for industrial flooring and prefabrications.

Basic **features**



Density: 7.8 kg/dm³



Diameter: 0.75 mm



Double hook geometry



Lenght: 50 mm



Unlimited shelf-life



Use wearing protective gloves



UV-resistant



Available **colours** Steel

Technical specifications

Aspect ratio (l / d): 67 _

Breaking load longitudinal: 1100 N/mm²

Effective length: 54.5 mm

Linear development (12 kg/m3): 3270 m/m³

Nominal length: 50 mm

Non-toxic material

Number of filmanets: 5000 nr/kg Static elastic modulus: 210000 N/mm²



www.azichem.com

Updated: 15/02/2021

General sales conditions and legal

notices on

www.azichem.com/disclaimer

Page: 1/2

Instructions for use

"READYMESH MX-500 fibres must be added to the concrete during mixing. It is recommended to pour the fibres directly onto the loading belt of the concrete mixer during the loading of the aggregates. Alternatively, it is possible to add them directly into the mixer after loading the concrete. In this case, add the fibres a little at a time so that they are well-distributed in the cement mix and extend the mixing time by at least one minute for every 20 kg of fibres added in order to achieve optimal distribution.

Conglomerates with READYMESH MX-500 can be easily transported and used with pumps, joiners, vibratory finishing machines, roadway extruders (e.g. slipform paver), etc."



Warnings, Precautions and Ecology

The general information, along with any instructions and recommendations for use of this product, including in this data sheet and eventually provided verbally or in writing, correspond to the present state of our scientific and practical knowledge.

Any technical and performance data reported is the result of laboratory tests conducted in a controlled environment and thus may be subject to modification in relation to the actual conditions of implementation.

Azichem Srl does not assume any liability arising from inadequate characteristics related to improper use of the product or connected to defects arising from factors or elements unrelated to the quality of the product, including improper storage.

Those wishing to utilise the product are required to determine prior to use whether or not the same is suitable for the intended use, assuming all consequent responsibility.

The technical and characteristic details contained in this data sheet shall be updated periodically. For consultation in real time, please visit the website: www.azichem.com. The date of revision is indicated in the space to the side. The current edition cancels out and replaces any previous version.

Please note that the user is required to read the latest Safety Data Sheet for this product, containing chemical-physical and toxicological data, risk phrases and other information regarding the safe transport, use and disposal of the product and its packaging. For consultation, please visit: www.azichem.com.

It is forbidden to dispose of the product and/or packaging in the environment.

READYMESH MX-500 is produced/distributed by





www.azichem.com

Updated: 15/02/2021
General sales conditions and legal

notices on

www.azichem.com/disclaimer

Page: 2/2